

#31 – Maintenance Standards for Permeable Pavement (BMP LID.09):

√	Drainage System Feature	Defect or Problem	Condition When Maintenance is Needed	Results Expected When Maintenance is Performed
	Facility – General Requirements	Unstable Adjacent Area	Runoff from adjacent pervious areas deposits soil, mulch, or sediment on paving.	No deposited soil or other materials on permeable pavement or other adjacent surfacing. All exposed soils that may erode to pavement surface mulched and/or planted.
	Facility – General Requirements	Wearing Course Covered by Adjacent Vegetation	Vegetation growing beyond facility edge onto sidewalks, paths, and street edge.	Vegetation does not impede function of adjacent facilities or pose as safety hazard. Groundcovers and shrubs trimmed to avoid overreaching the sidewalks, paths and street edge.
	Porous asphalt or pervious cement concrete	NA	None. Maintenance to prevent clogging with fine sediment.	Conventional street sweepers equipped with vacuums, water, and brushes or pressure washer used to restore permeability. Vacuum or pressure wash the pavement two to three times annually.
	Porous asphalt or pervious cement concrete	NA	None. Maintenance to prevent clogging with fine sediment.	Use of sand and sealant application prohibited. Protect from construction runoff.
	Porous asphalt or pervious cement concrete	Cracks	Major cracks or trip hazards.	Potholes or small cracks filled with patching mixes. Large cracks and settlement addressed by cutting and replacing the pavement section.
	Porous asphalt or pervious cement concrete	NA	Utility cuts.	Any damage or change due to utility cuts replaced in kind.
	All Pavement Types	Leaf and Debris Accumulation	Fallen leaves or debris.	Removed/disposed.
	Interlocking concrete paver blocks	Missing or Damaged Paver Block	Interlocking paver block missing or damaged.	Individual damaged paver blocks removed and replaced or repaired per manufacturer's recommendations.
	Interlocking concrete paver blocks	Settlement	Settlement of surface. When deviation from original grade impedes function.	Original grade re-established. May require resetting.
	All pavement types	All Pavement Types	Sediment or debris accumulation between paver blocks, on surface of pavement, or in grid voids.	Sediment at surface does not inhibit infiltration. Remove/dispose of sediment.

#31 – Maintenance Standards for Permeable Pavement (BMP LID.09):

√	Drainage System Feature	Defect or Problem	Condition When Maintenance is Needed	Results Expected When Maintenance is Performed
	Interlocking concrete paver blocks	Void material is missing or low	Loss of aggregate material between paver blocks.	Refill per manufacturer's recommendations.
	Open-celled paving grid with gravel	Loss of Aggregate Material in Paving Grid	Loss of aggregate material in grid.	Aggregate gravel level maintained at the same level as the plastic rings or no more than 0.25 inch above the top of rings. Refill per manufacturer's recommendations.
	Open-celled paving grid with grass	Lack of Grass Coverage	Loss of soil and/or grass material in grid.	Refill and/or replant per manufacturer's recommendations. Growing medium restored, facility aerated and reseeded or planted, and vegetated area amended as needed.
	Inlet/outlet pipe	Pipe is Damaged	Pipe is damaged.	Pipe is repaired/replaced.
	Inlet/outlet pipe	Pipe is Clogged	Pipe is clogged.	Roots or debris is removed.
	Inlet/outlet pipe	Erosion	Native soil exposed or other signs of erosion damage present.	No eroded or scoured areas Cause of erosion or scour is addressed.
	Underdrain pipe	Blocked Underdrain	Plant roots, sediment or debris reducing capacity of underdrain (may cause prolonged drawdown period).	Underdrains and orifice free of sediment and debris. Jet clean or rotary cut debris/roots from underdrain(s). If underdrains are equipped with a flow restrictor (e.g., orifice) to attenuate flows, the orifice must be cleaned regularly.
	Spill Prevention and Response	NA	Storage or use of potential contaminants in the vicinity of facility.	Spill prevention measures exercised whenever handling or storing potential contaminants.
	Spill Prevention and Response	Release of Pollutants	Any evidence of contaminants such as oil, gasoline, concrete slurries, paint, etc.	Spills are cleaned up as soon as possible to prevent contamination of stormwater. No contaminants or pollutants present. <i>(Coordinate removal/cleanup with Thurston County Water Resources 360-754-4681 and/or Thurston County Spill Hotline 360-239-8369.)</i>